

PHONE: 01793 611 777

EMAIL: [info@flytec.co.uk](mailto:info@flytec.co.uk)

**Atkore**<sup>™</sup>  
Unistrut

# Floor Systems



## Flush Floor Shallow Screeds

Flytec flush floor trunking body is supplied in 2 metre lengths complete with 2 x 1 metre lengths of lid secured by means of flush, all steel turnbuckle fasteners. Each length of trunking is supplied with one external fitting connector.

Lids are manufactured from 3mm thick galvanised steel. They are fully removable and may be flush or recessed by 3mm as standard. Other depths of recess can also be supplied.

It is advisable that all lid sections are fitted during screeding. This will prevent any slight inward movement to the sides of trunking body.

We recommend that Flytec flush floor trunking is installed on a ribbon screed or similar to ensure support along the entire length and width of the system.



**FLY**⚡**TEC**

SYSTEMS LIMITED



For more info visit [atkore.com/unistrut](http://atkore.com/unistrut) 

©2020 Atkore International, Inc. All rights reserved.

## Under Floor Trunking and Accessories

Flytec underfloor trunking is designed for placing on the constructional concrete slab, to be completely covered when the final floor screed is laid and the service outlet positions fixed.

Steel underfloor trunking manufactured in 2 metre lengths. Two or three compartment are most commonly used. Single or other numbers of compartments can also be supplied.

The trunking lengths are a total welded construction with no need to couple together loose channel sections.

Each length is joined together by a saddle clamp and plate, which prevent any ingress of screed into the duct.



## Chequer Plate Trunking and Accessories

When a flush floor trunking is required in an area where excessive loads will be transported such as a warehouse or industrial environment, Flytec manufacture a robust steel trunking body fitted with a 6mm thick chequer plate lid fixed into place by M6 countersunk screws.

Single or multi-compartment options are available with a range of accessories.

Because of the unique properties of this system to the installer, Flytec can make to order virtually any size of trunking and compartment configuration. Please contact us with your requirements.

We recommend that Flytec flush floor trunking is installed on a ribbon screed or similar to ensure support along the entire length and width of the system.

It is advisable that all lid sections are fitted during screeding. This will prevent any slight inward movement to the sides of trunking body.

Please note: Service boxes are not available with chequer plate trunking.

